

Polyester braided sleeve

TECHNICAL SPECIFICATIONS	TYPICAL VALUES	TESTING METHOD
tensile strenght	4.80 kg/mm ²	ISO 37
elongation at break	28–35 %	ISO 37
specific weight	1.38 g/cm ³	ISO R1183
water absorption	0.5% max	ASTM D570
self-extinguishing rating	HB	UL 94

Applications

- Protection and assembly of electrical, electronic and telephone cables
- Civil, industrial, and automotive wiring

Advantages

- Good mechanical resistance
- High tensile strength
- Removable
- Good resistance to chemicals
- Good resistance to UV rays

Features

- Tubular braided sleeve
- Premium quality single thread polyester
- Self-extinguishing HB according to UL 94
- Operating temperature: -50 / 170 °C
- Melting pot: 260 °C
- Non-toxic
- Halogen-free



COBRABOX

Polyester braided sleeve
in dispenser

- Handy package
- Colour grey

Selection table

item	rated diameter (mm)	diameter of ligation (mm)		Spool length (m)
		min	max	
COBRABOX 03	3	2	8	25
COBRABOX 04	4	3	9	25
COBRABOX 05	5	4	11	25
COBRABOX 06	6	5	15	25
COBRABOX 08	8	6	18	20
COBRABOX 10	10	8	21	20
COBRABOX 12	12	10	20	10
COBRABOX 15	15	12	29	10
COBRABOX 20	20	15	33	10
COBRABOX 25	25	20	45	10
COBRABOX 30	30	25	48	5
COBRABOX 40	40	35	60	3
COBRABOX 50	50	45	75	3

RHB



Polyester braided sleeve
in spool

- Available in grey and black

Selection table

item*	rated diameter (mm)	diameter of ligation (mm)		Spool length (m)
		min	max	
RHB 03	3	2	8	200
RHB 04	4	3	9	200
RHB 05	5	4	11	100
RHB 06	6	5	15	100
RHB 08	8	6	18	100
RHB 10	10	8	21	100
RHB 12	12	10	20	100
RHB 15	15	12	29	100
RHB 20	20	15	33	50
RHB 25	25	20	45	50
RHB 30	30	25	48	50
RHB 40	40	35	60	50
RHB 50	50	45	75	50

Available colours

- BK - Black ● GR - Grey

* To complete the item reference, add the colour code at the end
(eg. RHB-03-BK for the back sleeve RHB-03)