


GTAS

Thick wall heat shrink tubing sealant coated 4:1 cross-linked polyolefin - 1 meter bars

4:1	ref.	item	D/d (mm)	bar length (m)	thickness		cable diameter range (mm)	pack. (pcs)	min./ mult. ord. qty (pcs)
					T (mm)	t (mm)			
	GT40009	GTAS-12/3-1000/S	12/3	1.0	0.7	2.0	3.5 – 10	10	10
	GT40013	GTAS-16/4-1000/S	16/4	1.0	0.8	2.4	4.5 – 14	10	10
	GT40020	GTAS-24/6-1000/S	24/6	1.0	0.8	2.7	6.5 – 22	10	10
	GT40033	GTAS-34/8-1000/S	34/8	1.0	1.2	4.0	9 – 31	10	10
	GT40043	GTAS-48/12-1000/S	48/12	1.0	1.3	4.5	13 – 44	5	5
	GT40051	GTAS-56/16-1000/S	56/16	1.0	1.0	4.4	17.5 – 50	5	5
	GT40070	GTAS-70/20-1000/S	70/20	1.0	1.0	4.4	22 – 63	5	5
	GT40085	GTAS-90/25-1000/S	90/25	1.0	1.0	4.3	27 – 81	1	1
	GT40105	GTAS-110/30-1000/S	110/30	1.0	1.0	4.3	33 – 100	1	1
	GT40130	GTAS-130/35-1000/S	130/35	1.0	1.0	4.3	38 – 118	1	1
	GT40160	GTAS-160/50-1000/S	160/50	1.0	1.0	4.3	55 – 144	1	1
	GT40180	GTAS-180/50-1000/S	180/50	1.0	1.0	4.3	55 – 162	1	1

HEAT-SHRINK
TUBING



- D** Supplied diameter (before shrinkage)
- T** Thickness before shrinkage
- d** Recovered diameter (after free shrinkage)
- t** Recovered thickness (after free shrinkage)