



# Thin wall heat shrink tubing in spool

2:1 cross-linked polyolefin

GTUC 	item *	D/d (mm)	thickness t (mm)	cable diameter range min-max (mm)	colour						spool length (m)	min./ mult. ord.qty (m)	
					BLACK ● 0	RED ● 2	YELLOW ● 4	GREEN ● 5	BLUE ● 6	WHITE ● 9			CLEAR ● X
					ref.								
	GTUC-1,2/0,6	1,2/0,6	0,45	0,7 – 1,1	GT0012	GT2012	GT4012	GT5012	GT6012	GT9012	GTX012	300	300
	GTUC-1,6/0,8	1,6/0,8	0,45	1 – 1,4	GT0016	GT2016	GT4016	GT5016	GT6016	GT9016	GTX016	300	300
	GTUC-2,4/1,2	2,4/1,2	0,50	1,4 – 2,2	GT0024	GT2024	GT4024	GT5024	GT6024	GT9024	GTX024	150	150
	GTUC-3,2/1,6	3,2/1,6	0,50	1,9 – 2,9	GT0032	GT2032	GT4032	GT5032	GT6032	GT9032	GTX032	150	150
	GTUC-4,8/2,4	4,8/2,4	0,50	2,9 – 4,3	GT0048	GT2048	GT4048	GT5048	GT6048	GT9048	GTX048	150	150
	GTUC-6,4/3,2	6,4/3,2	0,65	3,8 – 5,8	GT0064	GT2064	GT4064	GT5064	GT6064	GT9064	GTX064	75	75
	GTUC-9,5/4,8	9,5/4,8	0,65	5,7 – 8,6	GT0095	GT2095	GT4095	GT5095	GT6095	GT9095	GTX095	75	75
	GTUC-12,7/6,4	12,7/6,4	0,65	7,7 – 11,4	GT0127	GT2127	GT4127	GT5127	GT6127	GT9127	GTX127	75	75
	GTUC-19/9,5	19/9,5	0,75	11,4 – 17,1	GT0019	GT2019	GT4019	GT5019	GT6019	GT9019	GTX019	75	75
	GTUC-25,4/12,7	25,4/12,7	0,90	15,2 – 22,9	GT0254	GT2254	GT4254	GT5254	GT6254	GT9254	GTX254	30	30
	GTUC-38/19	38/19	1,00	22,8 – 34,2	GT0038	GT2038	GT4038	GT5038	GT6038	GT9038	GTX038	30	30
	GTUC-51/25,4	51/25,4	1,15	30,5 – 45,9	GT0051	GT2051	GT4051	GT5051	GT6051	GT9051	GTX051	30	30
	GTUC-76/38	76/38	1,27	45,6 – 68,4	GT0076	GT2076	GT4076	GT5076	GT6076	GT9076	GTX076	15	15
	GTUC-102/51	102/51	1,40	61,2 – 91,8	GT0102	GT2102	GT4102	GT5102	GT6102	GT9102	GTX102	15	15

\* Add colour suffix to complete item identification  
(e.g. GTUC-1.2/0.6-0)

GTGV 	item	D/d (mm)	thickness t (mm)	cable diameter range min-max (mm)	colour	spool length (m)	min./ mult. ord.qty (m)
					YELLOW/GREEN ●		
					ref.		
	GTGV-3/1,5	3/1,5	0,51	1,8 – 2,7	GT3003	150	150
	GTGV-6/3	6/3	0,58	3,6 – 5,4	GT3006	75	75
	GTGV-8/4	8/4	0,64	4,8 – 7,2	GT3008	75	75
	GTGV-10/5	10/5	0,64	6 – 9	GT3010	75	75
	GTGV-12/6	12/6	0,64	7,2 – 10,8	GT3012	75	75
	GTGV-19/9	19/9	0,76	11 – 17	GT3019	75	75
	GTGV-26/13	26/13	0,89	15,6 – 23,4	GT3026	30	30
	GTGV-38/19	38/19	1,00	22,8 – 34,2	GT3038	30	30



**D** Supplied diameter (before shrinkage)  
**d** Recovered diameter (after free shrinkage)  
**t** Recovered thickness (after free shrinkage)