


3:1	ref.	item	D/d (mm)	bar length (m)	thickness		cable diameter range (mm)	pack. (pcs)	min./ mult. ord. qty (pcs)
					T (mm)	t (mm)			
	GT31010	GTMS-10/3-1000/S	10/3	1.0	0.3	1.0	3.5 – 9	10	10
	GT31016	GTMS-16/5-1000/S	16/5	1.0	0.3	1.4	5.5 – 14.5	10	10
	GT31025	GTMS-25/8-1000/S	25/8	1.0	0.4	2.0	9 – 22.5	10	10
	GT31035	GTMS-35/12-1000/S	35/12	1.0	0.4	2.0	13 – 31.5	10	10
	GT31050	GTMS-50/16-1000/S	50/16	1.0	0.5	2.0	18 – 45	5	5
	GT31063	GTMS-63/19-1000/S	63/19	1.0	0.6	2.4	21 – 57	5	5
	GT31075	GTMS-75/22-1000/S	75/22	1.0	0.6	2.7	24 – 68	5	5
	GT31085	GTMS-85/25-1000/S	85/25	1.0	0.6	2.8	28 – 77	1	1
	GT31095	GTMS-95/29-1000/S	95/29	1.0	0.7	3.1	32 – 86	1	1
	GT31115	GTMS-115/34-1000/S	115/34	1.0	0.7	3.1	37 – 104	1	1
	GT31140	GTMS-140/42-1000/S	140/42	1.0	0.7	3.1	46 – 126	1	1
	GT31160	GTMS-160/50-1000/S	160/50	1.0	0.7	3.2	55 – 144	1	1
	GT31180	GTMS-180/60-1000/S	180/60	1.0	0.7	3.2	66 – 162	1	1



- D** Supplied diameter (before shrinkage)
- T** Thickness before shrinkage
- d** Recovered diameter (after free shrinkage)
- t** Recovered thickness (after free shrinkage)