



# GTAS

## Guaine termorestringenti ad alto spessore con sigillante poliolefina reticolata 4:1 - barre da 1 metro

	codice	articolo	D/d (mm)	lungh. barra (m)	spessori		diam. ammissibile cavo min-max (mm)	conf. (pz)	min./mult. ord. (pz)
					S (mm)	s (mm)			
	GT40009	GTAS-12/3-1000/S	12/3	1,0	0,7	2,0	3,5 - 10	10	10
	GT40013	GTAS-16/4-1000/S	16/4	1,0	0,8	2,4	4,5 - 14	10	10
	GT40020	GTAS-24/6-1000/S	24/6	1,0	0,8	2,7	6,5 - 22	10	10
	GT40033	GTAS-34/8-1000/S	34/8	1,0	1,2	4,0	9 - 31	10	10
	GT40043	GTAS-48/12-1000/S	48/12	1,0	1,3	4,5	13 - 44	5	5
	GT40051	GTAS-56/16-1000/S	56/16	1,0	1,0	4,4	17,5 - 50	5	5
	GT40070	GTAS-70/20-1000/S	70/20	1,0	1,0	4,4	22 - 63	5	5
	GT40085	GTAS-90/25-1000/S	90/25	1,0	1,0	4,3	27 - 81	1	1
	GT40105	GTAS-110/30-1000/S	110/30	1,0	1,0	4,3	33 - 100	1	1
	GT40130	GTAS-130/35-1000/S	130/35	1,0	1,0	4,3	38 - 118	1	1
	GT40160	GTAS-160/50-1000/S	160/50	1,0	1,0	4,3	55 - 144	1	1
GT40180	GTAS-180/50-1000/S	180/50	1,0	1,0	4,3	55 - 162	1	1	



- D** Diametro prima del restringimento
- S** Spessore di fornitura
- d** Diametro dopo restringimento libero
- s** Spessore dopo restringimento libero