



DESCRIPTION

PVC high-performance insulating tape, black color, for insulation and protection of surfaces or conductors. The application does not require the use of heat or external pressure.

PRODUCT RANGE	
Series	4 PRO
Reference	NA8019
Commercial name	4 PRO

DIMENSION INFORMATION	
Width (W)	mm 19
Depth (D)	mm 0,15
Length (L)	m 25

PHYSICAL INFORMATION	
Material	Polyvinylchloride (PVC)
Color	Black
Operating temperature (min – max).	°C -10 ... + 90
Vulcanizing	No
Self-amalgamating	No
Self-extinguishing	Yes (CEI EN60454)
Halogen Free	(F), (Cl), (Br), (I), (At) Yes
Lead Free	Pb Yes
UV Resistant	n.d.

PRODUCT CONFORMITY			
		Nominal values	Standard
Maximum operating voltage	kV	0,6/1	EN 60454
Tensile strength	N/10mm	35	EN 60454
Elongation	%	300	EN 60454
Dielectric strength	kV/mm	45	EN 60454
Adhesiveness	N/10mm	2,5	EN 60454

PRODUCT CONFORMITY	
Certifications	IMQ
Standard reference	EN 60454-3-1
Conformity	Directive 2011/65/EU (RoHS 2) and 2015/863/UE (RoHS 3)
Fire resistance	n.a.
ETIM classification	Ver. 9.0 EC000128

SAFETY INFORMATION

Harmful product	No
Dangerous product	No
CLP compliant (Regulation 1272/2008/CE)	n.a.

LOGISTIC INFORMATION

Single product	Barcode	1 pc	EAN 13	8053323905608
	Dimensions (L x W x H)	1 pc	m	0,080 x 0,020
	Weight	1 pc	kg	0,095
Packaging	Barcode	120 pc	EAN 13	8053323905615
	Dimensioni (L x W x H)	120 pc	m	0,315 x 0,245 x 0,215
	Weight	120 pc	kg	11,60

HS code 39191012

Origin RPC

**NOTE**

These information and our technical indications correspond to our knowledge and experience without however constituting our guarantee in relation to the final results or responsibilities deriving from any legal relationship. In fact, considering the multiplicity of materials, handling and storage conditions, as well as production and use conditions, all the information and indications above must be previously verified by the user according to his specific circumstances of use.